

Solder Pot Exchange and Service Cart

Increased Accessibility and Rapid Solder Alloy Changeover


Features and Benefits

- Portable cart to facilitate servicing and rapid changeover between solder alloys as well as provide access to internal machine functions
- Minimizes machine downtime by exchanging solder pots while pots remaining hot but not molten to minimize solder spills
- Solder pots of different solder alloys can be exchanged in less than 10 minutes
- Has capacity to carry two tin-lead, lead-free or HMP solder pots simultaneously reducing the time to exchange solder pots
- Compatible with all Nordson SELECT Novo™, Cerno™ and Integra™ selective soldering machines equipped for service cart

Overview. The Solder Pot Exchange and Service Cart can be used for servicing solder pots or for rapid exchange of solder pots with different solder alloys. Solder pots are exchanged while hot, but the solder is not molten to avoid solder spills and minimize machine downtime. The actual exchange time is approximately ten minutes when changing between various solder alloys.



Solder pot exchange cart with two solder pots in place



Integrated Solution. The Solder Pot Exchange and Service Cart fully integrates with closed-loop process controls embedded in Nordson SELECT's SWAK-OS 4.0 software providing seamless operation for your selective soldering process. Nordson SELECT's closed-loop process controls enable successful results for a full range of soldering applications and ensures stable and repeatable results for high-yield production.

Experience. With over a decade of selective soldering experience and more than a thousand systems currently in production, Nordson SELECT is committed to providing innovative solutions for all selective soldering needs. Our global support network, including state-of-the-art application development labs, provides customers with world-class know-how and application expertise.

Solder Pot Exchange and Service Cart

Dimensions

Width:	406 mm (16 in.)
Length:	1118 mm (44 in.)
Height:	762 mm (30 in.)

Facilities Requirements

Standard:	120VAC, 60 Hz, single phase, 8 A
Optional:	220VAC, 60 Hz, single phase, 5 A

For more information, speak with your local representative or contact your regional office.

Nordsonselect.com

North America

Headquarters

Liberty Lake, WA, USA

+1.509.924.4898

sales.usa@nordsonselect.com

China

Email:

info.cn@nordsonselect.com

Shanghai

+86.21.3866.9166

Beijing

+86.10.8453.6388

Guangzhou

+86.20.8554.9996

Europe

Maastricht, Netherlands

+31.43.352.4466

info.eu@nordsonselect.com

Japan

Tokyo

+81.3.3599.5920

Info.japan@nordsonselect.com

Korea

Seoul

+82.31.765.8337

info.kr@nordsonselect.com

India

Chennai

+91.44.4353.9024

info.in@nordsonselect.com

S.E. Asia/Australia

Singapore

+65.6796.9514

info.sg@nordsonselect.com

Taiwan

+886.229.02.1860

info.tw@nordsonselect.com

Nordson SELECT, Inc.

+1.509.924.4898 Phone

sales.usa@nordsonselect.com Email

22425 East Appleway Avenue

Liberty Lake, WA USA 99019-8508

www.nordsonselect.com

Published 2018-30-05