

Nova Spray

isopentane S

INVENTEC
PERFORMANCE CHEMICALS



PERFORMANCES

Highly pure, specially deodorized, the NovaSpray™ isopentane S may be used in cosmetic formulations. With a constant quality, it meets all the requirements of a solvent.

The solubility of resins in **NovaSpray™ isopentane S** and of most components insoluble in butanes/propane along with its miscibility with most polar or non polar solvents allows a **wide formulation range**.

Economical thanks to its low density, **it replaces advantageously ethanol as a solvent.**
Its low boiling point is a plus in specific formulations.

With no effect on the ozone layer and a negligible impact on the greenhouse effect.

SPECIFICATIONS

Standard Characteristics	Limit values
Appearance	clear
Purity	≥ 95 % weight
Benzene	≤ 2 ppm weight
Bromine index	≤ 50 mg /100 g
Colour Saybolt	30
Non-volatile residue	≤ 10 g/m ³
Sulfur	≤ 1 ppm weight

CHARACTERISTICS

		Units	Values
Chemical Formula			(CH ₃) ₂ CHCH ₂ CH ₃
Molecular weight		g/mol	72,15
Boiling point	at 1,013 bar	°C	27,8
Liquid density	at 20°C	kg/dm ³	0,620
	at 50°C	kg/dm ³	0,582
Absolute pressure	saturation vapor at 20°C	bar	0,770
	saturation vapor at 50°C	bar	2,030
Flash point	closed cup	°C	< -51
Lower flammability limit	in the air at 20°C at 1,013 bar	% volume	1,3
Upper flammability limit			7,6
Auto-ignition temperature		°C	> 200

THE BEST SOLUTION FOR COSMETICS APPLICATIONS

Inventec is very attentive to the extreme quality required for cosmetic applications by the main actors in this field. That is why we have improved our process in order to satisfy you with a NOVASPRAY Isopentane S.



Inventec developed a molecular sieve to purify Isopentane.

In hydrocarbons, like isopentane, the main problem responsible for the odour is the presence of sulfur compound, because once isopentane is blend with water, sulfur compounds become odorous.

Now all the deliveries of NovaSpray isopentane S pass through the molecular sieve. It has been developed to purify the isopentane S.



PACKAGING

	Drum	Container	Bulk
Capacity (liter)	217	930	5 to 20 T
Tare (kg)	22	460	
Load (kg)	120	450	
Diameter (mm)	585	860	
Height (mm)	880	2330	
Outflow external diameter (mm)	3/4" and 2"	26,1	
Tap : left pitch (mm)	---	1,814	
Test pressure (bar)	---	33	

- Packaging technical characteristics are available upon request to the commercial department.
- Feasibility of filling packaging of the customers if they are in conformity with the legislation.
- Contact us for any other specific packaging.

STORAGE AND SHELF LIFE

Precautions for handling and storage:

French plants are controlled by the regulation of listed Establishments and have to comply with it (or with the local legislation).

- All packaging will be stored in a dry, well ventilated, easily accessible place, sheltered from sunlight and bad weather, away from any ignition source.
- It is recommended to store all packaging either in a specific place or isolated and sheltered by a fence.
- All packaging and piping will be grounded to discharge static electricity.
- Leak detectors, put at ground level, will be connected to an audible alarm, which will trigger in the event of leaks.
- The whole equipment will be tested with an appropriate leak detector before use.
- Material and electrical equipment in an explosive atmosphere will comply with the regulations (*grounding, equipotential bonding, ATEX material*).

INVENTEC can study the set up and assembling of your storage tanks, piping, and pumps, according to the prevailing regulations

CONDITIONS OF USE

Please refer to the Material Safety Data Sheet (MSDS) before using the product. Workers handling the product should be trained about risks and preventive measures.

The NovaSpray™ isopentane S is compatible with:

- The following plastics:
 - Polyethylene
 - Polypropylene
 - Polyester
 - Teflon
- The following metals :
 - Carbon steel
 - Stainless steel

The NovaSpray™ isopentane S is not compatible with:

- Rubbers (natural or butyl)
- Polystyrene
- Oxidizing agents
- Combustive agents

Measures while handling:

- Collect vapors at emission point.
- Use spark-free tools (*beryllium bronze*).
- Ground the equipment.
- Work in a well ventilated place to avoid accumulating static discharges.

HEALTH SAFETY ENVIRONMENT (HSE)

Consult the Material Safety Datasheet (MSDS) on the website : www.quickfds.com

This data is based on information that the manufacturer believed to be reliable and offered in good faith. On no account, Inventec will be responsible for special, incidental and consequential damages. The user is responsible, to the Administrative Authorities (Regulation of the listed establishments for the protection of the environment), for the conformity of his installation.