

**X-Treme
Series**

AUTO DRY CABINETS

**CABINET MODELS
& ACCESSORIES**

2020



0.5%Rh
Humidity

100°C
Temperature

www.x-tremeseries.com

AUTO DRY CABINETS

XT-LINE CABINETS

(1250 Liters)



CABINET MODELS & ACCESSORIES 2020

1200(w) X 1990(h) X 750(d)mm ◀.....

MODEL	DESCRIPTION (STANDARD & OPTIONS)
XT Line Dehumidifier Cabinets - 1250 Liters	
XTC-510-01 BASIC with 1 Dehumidifier Unit Version 3.0	<ul style="list-style-type: none"> • 1 ea Dehumidifier Unit • Internal Humidity and Temperature Sensor • 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable • Remote Monitoring System (RMS) • Datalogger (2GB) • 10 x Stainless Steel (SS) Shelves • Door Alarm with Buzzer • 4 x Doors Double Insulated Glass • Rear Stainless Steel (SS) Panels • 4 x Casters (2 of them are lockable) • Adjustable Stabilization Legs 2 pcs • Electrostatic Painted Metal Sheet Body - 1250 Liters Net
XTC-520-01 BASIC with 2 Dehumidifier Unit Version 3.0	<ul style="list-style-type: none"> • 2 ea Dehumidifier Unit • Internal Humidity and Temperature Sensor • 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable • Remote Monitoring System (RMS) • Datalogger (2GB) • 10 x Stainless Steel (SS) Shelves • Door Alarm with Buzzer • 4 x Doors Double Insulated Glass • Rear Stainless Steel (SS) Panels • 4 x Casters (2 of them are lockable) • Adjustable Stabilization Legs 2 pcs • Electrostatic Painted Metal Sheet Body - 1250 Liters Net
XTC-510-S1 STANDARD CABINET 1 Version 3.0	<ul style="list-style-type: none"> • 1 ea Dehumidifier Unit • Indoor Light (XT-LGK-01) • Internal Humidity and Temperature Sensor • 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable • Remote Monitoring System (RMS) • Datalogger (2GB) • 10 x Stainless Steel (SS) Shelves • Door Alarm with Buzzer • 4 x Doors Double Insulated Glass • Rear Stainless Steel (SS) Panels • 4 x Casters (2 of them are lockable) • Adjustable Stabilization Legs 2 pcs • Electrostatic Painted Metal Sheet Body - 1250 Liters Net
XTC-510-S2 STANDARD CABINET 2 Version 3.0	<ul style="list-style-type: none"> • 1 ea Dehumidifier Unit • Indoor Light (XT-LGK-01) • Heater Kit (45 °C) Thermal Insulation and Only Stainless Steel (SS) BACK PANELS (XT-HTK-01) • Internal Humidity and Temperature Sensor • 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable • Remote Monitoring System (RMS) • Datalogger (2GB) • 10 x Stainless Steel (SS) Shelves • Door Alarm with Buzzer • 4 x Doors Double Insulated Glass • Rear Stainless Steel (SS) Panels • 4 x Casters (2 of them are lockable) • Adjustable Stabilization Legs 2 pcs • Electrostatic Painted Metal Sheet Body - 1250 Liters Net

<p>XTC-510-S3 STANDARD CABINET 3 Version 3.0</p>	<ul style="list-style-type: none"> • 1 ea Dehumidifier Unit • Indoor Light (XT-LGK-01) • Heater Kit (60 °C) and Double Wall Thermal Insulation and (SS) Panels ALL Sides (XT-HTK-02) • Outside Humidity and Temperature Sensor (HTS-02) • Internal Humidity and Temperature Sensor • 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable • Remote Monitoring System (RMS) • Datalogger (2GB) • 10 x Stainless Steel (SS) Shelves • Door Alarm with Buzzer • 4 x Doors Double Insulated Glass • Rear Stainless Steel (SS) Panels • 4 x Casters (2 of them are lockable) • Adjustable Stabilization Legs 2 pcs • Electrostatic Painted Metal Sheet Body - 1250 Liters Net
<p>XTC-510-S4 STANDARD CABINET 4 Version 3.0</p>	<ul style="list-style-type: none"> • 1 ea Dehumidifier Unit • Indoor Light (XT-LGK-01) • Heater Kit (60 °C) and Double Wall Thermal Insulation and (SS) Panels ALL Sides (XT-HTK-02) • Outside Humidity and Temperature Sensor (HTS-02) • AUTO Door Locks (DLK-04) • Internal Humidity and Temperature Sensor • 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable • Remote Monitoring System (RMS) • Datalogger (2GB) • 10 x Stainless Steel (SS) Shelves • Door Alarm with Buzzer • 4 x Doors Double Insulated Glass • Rear Stainless Steel (SS) Panels • 4 x Casters (2 of them are lockable) • Adjustable Stabilization Legs 2 pcs • Electrostatic Painted Metal Sheet Body - 1250 Liters Net
<p>XTC-520-S5 STANDARD CABINET 5 Version 3.0</p>	<ul style="list-style-type: none"> • 2 ea Dehumidifier Unit • Indoor Light (XT-LGK-01) • Internal Humidity and Temperature Sensor • 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable • Remote Monitoring System (RMS) • Datalogger (2GB) • 10 x Stainless Steel (SS) Shelves • Door Alarm with Buzzer • 4 x Doors Double Insulated Glass • Rear Stainless Steel (SS) Panels • 4 x Casters (2 of them are lockable) • Adjustable Stabilization Legs 2 pcs • Electrostatic Painted Metal Sheet Body - 1250 Liters Net
<p>XTC-520-S6 STANDARD CABINET 6 Version 3.0</p>	<ul style="list-style-type: none"> • 2 ea Dehumidifier Unit • Indoor Light (XT-LGK-01) • Heater Kit (45 °C) Thermal Insulation and Only Stainless Steel (SS) BACK PANELS (XT-HTK-01) • Internal Humidity and Temperature Sensor • 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable • Remote Monitoring System (RMS) • Datalogger (2GB) • 10 x Stainless Steel (SS) Shelves • Door Alarm with Buzzer • 4 x Doors Double Insulated Glass • Rear Stainless Steel (SS) Panels • 4 x Casters (2 of them are lockable) • Adjustable Stabilization Legs 2 pcs • Electrostatic Painted Metal Sheet Body - 1250 Liters Net

XTC-520-S7
STANDARD
CABINET 7
Version 3.0

- 2 ea Dehumidifier Unit
- Indoor Light (XT-LGK-01)
- Heater Kit (60 °C) and Double Wall Thermal Insulation and (SS) Panels ALL Sides (XT-HTK-02)
- Outside Humidity and Temperature Sensor (HTS-02)
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- 10 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 4 x Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body - 1250 Liters Net

XTC-520-S8
STANDARD
CABINET
Version 3.0

- 2 ea Dehumidifier Unit
- Indoor Light (XT-LGK-01)
- Heater Kit (60 °C) and Double Wall Thermal Insulation and (SS) Panels ALL Sides (XT-HTK-02)
- Outside Humidity and Temperature Sensor (HTS-02)
- AUTO Door Locks (DLK-04)
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- 10 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 4 x Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body - 1250 Liters Net

XT Line Smart Nitrogen (N2) Cabinets - With N2 Auto Flow System Only / 1250 Liters

XTC-N2
BASIC with N2
Auto Flow Unit
Version 3.0

- 1 ea N2 Auto Flow Unit
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- 10 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 4 x Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body - 1250 Liters Net

XT Line Hybrid Cabinets - With N2 Auto Flow System + Dehumidifier Unit / 1250 Liters

XTC-510-DN2
BASIC with
Dehumidifier and
N2 Auto Flow
Unit
Version 3.0

- 1 ea Dehumidifier Unit
- 1 ea N2 Auto Flow Unit
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- 10 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 4 x Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body - 1250 Liters Net

<p>XTC-520-DN2 BASIC with 2 Dehumidifier and N2 Auto Flow Unit Version 3.0</p>	<ul style="list-style-type: none"> • 2 ea Dehumidifier Unit • 1 ea N2 Auto Flow Unit • Internal Humidity and Temperature Sensor • 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable • Remote Monitoring System (RMS) • Datalogger (2GB) • 10 x Stainless Steel (SS) Shelves • Door Alarm with Buzzer • 4 x Doors Double Insulated Glass • Rear Stainless Steel (SS) Panels • 4 x Casters (2 of them are lockable) • Adjustable Stabilization Legs 2 pcs • Electrostatic Painted Metal Sheet Body - 1250 Liters Net
---	--

OPTIONS FOR XT LINE (Please add options to basic models to get desired configuration)

XT-HTK-01	Heater Kit (45 °C) for XT Line, Thermal Insulation and Only Stainless Steel (SS) BACK PANELS - NO Stainless Steel (SS) Panels on the Left Side, Right Side, Bottom and Top
XT-HTK-02	Heater Kit (60 °C) for XT Line, Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
XT-HTK-03	Heater Kit (100 °C) for XT Line, Reinforced Heating Unit and Fans. Full Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
XT-DR2-01	Two Door Option for XT Line
SSS-01	Stainless Steel (SS) Shelf for XT Line (2 each required for one level)
SD-01	Stainless Steel (SS) Sliding Shelf for XT Line (2 each required for one level)
DLK-04	Automatic Door Locks by Password for XT and XL Line
XT-LGK-01	Indoor Light for XT Line
XT-FS-01**	Custom Sliding Feeder Storage Solutions for XT Line

CABINET MODELS & ACCESSORIES 2020

AUTO DRY CABINETS

XS-LINE CABINETS

XSC-300 (300 Liters) / XSC-600 (625 Liters) /
XSC-900 (925 Liters)

CABINET MODELS & ACCESSORIES 2020

606(w) X 1990(h) X 750(d)mm

606(w) X 1128(h) X 750(d)mm



MODEL	DESCRIPTION (STANDARD & OPTIONS)
XS Line Dehumidifier Cabinets-300 Liters XSC-300/ 625 Liters XSC-600/ 925 Liters XSC-900	
<p>XSC-300-01 BASIC with 1 Dehumidifier Unit Version 3.0</p>	<ul style="list-style-type: none"> • 1 ea Dehumidifier Unit • Internal Humidity and Temperature Sensor • 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable • Remote Monitoring System (RMS) • Datalogger (2GB) • 2 x Stainless Steel (SS) Shelves • Door Alarm with Buzzer • 1 Door Double Insulated Glass • Rear Stainless Steel (SS) Panels • 4 x Casters (2 of them are lockable) • Adjustable Stabilization Legs 2 pcs • Electrostatic Painted Metal Sheet Body - 300 Liters Net
<p>XSC-600-01 BASIC with 1 Dehumidifier Unit Version 3.0</p>	<ul style="list-style-type: none"> • 1 ea Dehumidifier Unit • Internal Humidity and Temperature Sensor • 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable • Remote Monitoring System (RMS) • Datalogger (2GB) • 5 x Stainless Steel (SS) Shelves • Door Alarm with Buzzer • 2 Doors Double Insulated Glass • Rear Stainless Steel (SS) Panels • 4 x Casters (2 of them are lockable) • Adjustable Stabilization Legs 2 pcs • Electrostatic Painted Metal Sheet Body - 625 Liters Net
<p>XSC-900-01 BASIC with 1 Dehumidifier Unit Version 3.0</p>	<ul style="list-style-type: none"> • 1 ea Dehumidifier Unit • Internal Humidity and Temperature Sensor • 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable • Remote Monitoring System (RMS) • Datalogger (2GB) • 5 x Stainless Steel (SS) Shelves • Door Alarm with Buzzer • 2 Doors Double Insulated Glass • Rear Stainless Steel (SS) Panels • 4 x Casters (2 of them are lockable) • Adjustable Stabilization Legs 2 pcs • Electrostatic Painted Metal Sheet Body - 925 Liters Net
XS Line Smart Nitrogen (N2) Cabinets - With N2 Auto Flow System Only 300 Liters XSC- 300 / 625 Liters XSC-600 / 925 Liters XSC-900	
<p>XSC-300-N2 BASIC with N2 Auto Flow Unit Version 3.0</p>	<ul style="list-style-type: none"> • 1 ea N2 Auto Flow Unit • Internal Humidity and Temperature Sensor • 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable • Remote Monitoring System (RMS) • Datalogger (2GB) • 2 x Stainless Steel (SS) Shelves • Door Alarm with Buzzer • 1 Door Double Insulated Glass • Rear Stainless Steel (SS) Panels • 4 x Casters (2 of them are lockable) • Adjustable Stabilization Legs 2 pcs • Electrostatic Painted Metal Sheet Body - 300 Liters Net

XSC-600-N2

BASIC with N2
Auto Flow Unit
Version 3.0

- 1 ea N2 Auto Flow Unit
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- 5 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 2 Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body - 625 Liters Net

XSC-900-N2

BASIC with N2
Auto Flow Unit
Version 3.0

- 1 ea N2 Auto Flow Unit
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- 5 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 2 Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body - 925 Liters Net

XS Line Hybrid Cabinets - With N2 Auto Flow System + Dehumidifier Unit
300 Liters XSC- 300 / 625 Liters XSC-600 / 925 Liters XSC-900

XSC-300-DN2

BASIC with 1
Dehumidifier and
N2 Auto Flow
Unit
Version 3.0

- 1 ea Dehumidifier Unit
- 1 ea N2 Auto Flow Unit
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- 2 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 1 Door Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body - 300 Liters Net

XSC-600-DN2

BASIC with 1
Dehumidifier and
N2 Auto Flow
Unit
Version 3.0

- 1 ea Dehumidifier Unit
- 1 ea N2 Auto Flow Unit
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- 5 x Stainless Steel (SS) Shelves
- Door Alarm with Buzzer
- 2 Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 4 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body - 625 Liters Net

XSC-900-DN2 BASIC with 1 Dehumidifier and N2 Auto Flow Unit Version 3.0	<ul style="list-style-type: none"> • 1 ea Dehumidifier Unit • 1 ea N2 Auto Flow Unit • Internal Humidity and Temperature Sensor • 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable • Remote Monitoring System (RMS) • Datalogger (2GB) • 5 x Stainless Steel (SS) Shelves • Door Alarm with Buzzer • 2 Doors Double Insulated Glass • Rear Stainless Steel (SS) Panels • 4 x Casters (2 of them are lockable) • Adjustable Stabilization Legs 2 pcs • Electrostatic Painted Metal Sheet Body - 925 Liters Net
---	--

OPTIONS FOR XS LINE (Please add options to basic models to get desired configuration)

XS-HTK-01	Heater Kit (45 °C) for XS Line, Thermal Insulation and Only Stainless Steel (SS) BACK PANELS - NO Stainless Steel (SS) Panels on the Left Side, Right Side, Bottom and Top
XS-HTK-02	Heater Kit (60 °C) for XSC-300, Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
XS-HTK-03	Heater Kit (60 °C) for XSC-600, Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
XS-HTK-04	Heater Kit (60 °C) for XSC-900, Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
XS-HTK-05	Heater Kit (100 °C) for XSC-300, Reinforced Heating Unit and Fans. Full Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
XS-HTK-06	Heater Kit (100 °C) for XSC-600, Reinforced Heating Unit and Fans. Full Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
XS-HTK-07	Heater Kit (100 °C) for XSC-900, Reinforced Heating Unit and Fans. Full Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
SSS-01	Stainless Steel (SS) Shelf for XSC-300 and XSC-600
SSS-02	Stainless Steel (SS) Shelf for XSC-900
SD-01	Stainless Steel (SS) Sliding Shelf for XSC-300 and XSC-600
SD-02	Stainless Steel (SS) Sliding Shelf for XSC-900
DLK-01	Automatic Door Locks by Password for XSC-300
DLK-02	Automatic Door Locks by Password for XSC-600 and XSC-900
XS-LGK-01	Indoor Light for XSC-300
XS-LGK-02	Indoor Light for XSC-600 and XSC-900
XS-DOR-01	1 Door Option for XSC-600
XS-FS-01	Custom Sliding Feeder Storage Solutions for XS Line

***CABINET MODELS
& ACCESSORIES 2020***

AUTO DRY CABINETS

XL-LINE CABINETS

(1840 Liters)



CABINET MODELS & ACCESSORIES 2020

1200(w) X 1990(h) X 1050(d)mm ←.....

MODEL	DESCRIPTION (STANDARD & OPTIONS)
XL Line Dehumidifier Cabinets - 1840 Liters	
<p>XLC-01 BASIC with 1 Dehumidifier Unit Version 3.0</p>	<ul style="list-style-type: none"> • 1 ea Dehumidifier Unit • Internal Humidity and Temperature Sensor • 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable • Remote Monitoring System (RMS) • Datalogger (2GB) • No Shelves • Door Alarm with Buzzer • 2 Doors Double Insulated Glass • Rear Stainless Steel (SS) Panels • 6 x Casters (2 of them are lockable) • Adjustable Stabilization Legs 2 pcs • Electrostatic Painted Metal Sheet Body, Depth (93 cm Net) - 1840 liters Net • Cabinet suitable for Long FEEDER Storage Solutions - Pls add options below
<p>XLC-02 BASIC with 2 Dehumidifier Unit Version 3.0</p>	<ul style="list-style-type: none"> • 2 ea Dehumidifier Unit • Internal Humidity and Temperature Sensor • 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable • Remote Monitoring System (RMS) • Datalogger (2GB) • No Shelves • Door Alarm with Buzzer • 2 Doors Double Insulated Glass • Rear Stainless (SS) Steel Panels • 6 x Casters (2 of them are lockable) • Adjustable Stabilization Legs 2 pcs • Electrostatic Painted Metal Sheet Body, Depth (93 cm Net) - 1840 liters Net • Suitable for Long FEEDER Storage Solutions - Pls add options below
XL Line Smart Nitrogen (N2) Cabinets - With N2 Auto Flow System Only 1840 Liters	
<p>XLC-N2 BASIC with N2 Auto Flow Unit Version 3.0</p>	<ul style="list-style-type: none"> • 1 each N2 Auto Flow Unit • Internal Humidity and Temperature Sensor • 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution • Internet Connection by Wi-Fi or Ethernet Cable • Remote Monitoring System (RMS) • Datalogger (2GB) • No Shelves • Door Alarm with Buzzer • 2 Doors Double Insulated Glass • Rear Stainless (SS) Steel Panels • 6 x Casters (2 of them are lockable) • Adjustable Stabilization Legs 2 pcs • Electrostatic Painted Metal Sheet Body, Depth (93 cm Net) - 1840 liters Net • Suitable for Long FEEDER Storage Solutions - Pls add options below

*** Shelves are not included to the XL Line Cabinets in order to enable customized storage solutions.

XL Line Hybrid Cabinets - With N2 Auto Flow System + Dehumidifier Unit 1840 Liters

XLC-510-DN2 BASIC with Dehumidifier and N2 Auto Flow Unit Version 3.0

- 1 each Dehumidifier Unit
- 1 each N2 Auto Flow Unit
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- No Shelves
- Door Alarm with Buzzer
- 2 Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 6 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body, Depth (93 cm Net) - 1840 liters Net
- Suitable for Long FEEDER Storage Solutions - Pls add options below

XLC-520-DN2 BASIC with 2 Dehumidifier and N2 Auto Flow Unit Version 3.0

- 2 each Dehumidifier Unit
- 1 each N2 Auto Flow Unit
- Internal Humidity and Temperature Sensor
- 7" Touch Screen Control Panel, 800*480 Pixel Screen Resolution
- Internet Connection by Wi-Fi or Ethernet Cable
- Remote Monitoring System (RMS)
- Datalogger (2GB)
- No Shelves
- Door Alarm with Buzzer
- 2 Doors Double Insulated Glass
- Rear Stainless Steel (SS) Panels
- 6 x Casters (2 of them are lockable)
- Adjustable Stabilization Legs 2 pcs
- Electrostatic Painted Metal Sheet Body, Depth (93 cm Net) - 1840 liters Net
- Suitable for Long FEEDER Storage Solutions - Pls add options below

*** *Shelves are not included to the XL Line Cabinets in order to enable customized storage solutions.*

OPTIONS FOR XL LINE (Please add options to basic models to get desired configuration)

XL-HTK-01	Heater Kit (45 °C) for XL Line, Thermal Insulation and Only Stainless Steel (SS) BACK PANELS - NO Stainless Steel (SS) Panels on the Left Side, Right Side, Bottom and Top
XL-HTK-02	Heater Kit (60 °C) for XL Line, Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
XL-HTK-03	Heater Kit (100 °C) for XL Line, Reinforced Heating Unit and Fans. Full Double Wall Thermal Insulation and Stainless Steel (SS) Panels ALL Sides (Left Side, Right Side, Bottom, Top, Back)
SSS-02	Stainless Steel (SS) Shelf for XL Line, x (2 required for one level)
SD-02	Stainless Steel (SS) Sliding Shelf for XL Line, x (2 required for one level)
XL-LGK-01	Indoor Light for XL Line
DLK-04	Automatic Door Locks by Password for XT and XL Line
XL-DR4-01	Four Door Option for XL Line
XL-FS-01**	Custom Sliding Feeder Storage Solution for XL Line

OPTIONS & ACCESSORIES

Options are valid for all cabinet models

RF-01	RFID Access
V3-01	Embedded Software Upgrade to Version 3.0 from Version 2.0
MSDTrack	MSD (Moisture Sensitive Device) Traceability Software
PCB-01	PCB Holder
XT-DSSU-03	Stainless Steel (SS) U Divider for XT Line XSC-300 and XSC-600
XT-DSSI-04	Stainless Steel (SS) I Divider for XT Line XSC-300 and XSC-600
XL-DSSU-03	Stainless Steel (SS) U Divider for XL Line and XSC-900
XL-DSSI-04	Stainless Steel (SS) I Divider for XL Line and XSC-900
SMDD-01	Stainless Steel (SS) SMD Reel Holder with 20 Divider Wire
LEG-01	Adjustable Stabilization Legs 2 pcs
XS-EXT-01	Extraction Unit for XSC-300 and XSC-600
XS-EXT-02	Extraction Unit for XSC-900
XT-EXT-01	Extraction Unit for XT Line
XL-EXT-01	Extraction Unit for XL Line
HTS-02	Outside Humidity and Temperature Sensor
EAL-01	External Alarm Bar with Magnetic Base, 2-Color Light and Buzzer
N2AF-01	N2 Auto Flow System
COAF-01	Cooling Unit
HUM-01	Humidifier Unit
HEPA-01	Hepa Filter Option-Class 1000 (ISO 6)
**	Please ask first before quoting to Customer

CABINET MODELS & ACCESSORIES 2020