



Compatible  
**[SMARTBOX]**  
 <PROCESS TRACKER>



## Classic-BUFC-460 - 25P

### FEATURES

This vertical buffer is designed to have the function as FIFO/ LIFO and by-pass functions. This unit is located between SMT machines to improve the working efficiency by buffering.

- PCB Max : 500x460
- PLC program control
- Servo motor system to improve the working efficiency
- Selectable pitch settings
- Tower-light display for machines working status.
- Built-in Rack structure
- Enclosed CE construction to improve the safety level
- Conveyor & rack adjustment by motorized
- Separately driven buffer conveyors
- 20 PCBs storage capacity
- Use the friendly touch screen panel
- SMEMA compatible
- Threshold signal to protect the PCBs in the upstream oven

Transfer heights	900mm+/-50mm
Transfer direction	Left to right
Operation side	Front of machine
Fixed rail	Front of machine
Interface	SMEMA
Conveyor belts	ESD flat belt
PCB edge support	3mm
Allowable components clearance	25mm below and above
Slots distance	25mm
Width adjustment method	Motorized type
Boards stock capacity	20 PCS
Air supply	4-6 bar
Safety	CE certificates
Control	PLC
Voltage	220V/ 110V , single phase, 50-60Hz

## GLOBAL NETWORK

**FACTORYCENTER**  
 SEOUL - BARCELONA

**BUSINESSCENTER**  
 KOREA - MEXICO - GERMANY  
 FRANCE - SPAIN - PORTUGAL - TUNISIA

**TESTCENTER**  
 KOREA - SPAIN - FRANCE

**FACTORYCENTER**  
**BARCELONA**

Ctra. C-31, 148,4. Masia Les Planes, 20.  
 Camí de Les Planes. 08880 Cubelles,  
 Barcelona. Spain  
[administrative@mstechcorp.eu](mailto:administrative@mstechcorp.eu)

**BUSINESSCENTER**

[sales@mstechcorp.eu](mailto:sales@mstechcorp.eu)  
[services@mstechcorp.eu](mailto:services@mstechcorp.eu)


**MSTECH**  
 EUROPE
