



Compatible
[SMARTBOX]
 <PROCESS TRACKER>



Classic-CL-390

This multi magazine unloader is design special for the coating line, all the machine will be with the seal cover and be equipped with the extraction for the vapors of the coating line.

FEATURES

- PCB Max : 530x390
- External air extraction stop alarm system.
- Full seal cover to enhance the safety friendly working environment in the coating line.
- Panasonic PLC program control
- Selectable pitch settings : 10mm to 80mm
- Tower-light display for machines working status.
- Flexible platform to suit standard magazines
- Exchangeable magazine from the rear of magazine
- Stepper motorized type pusher to enhance working stability
- Pusher position adjustable to Centre for the boards
- Use the friendly touch screen panel
- Magazine infeed and outfeed are automatically driving by motor on the platform.
- SMEMA compatible

<PROCESS TRACKER>

Transfer heights	900mm+/-50mm
Transfer direction	Left to right
Lifting platform Max. weight loading	Above 150kg
Operation side	Front of machine
Fixed rail	Front of machine
Interface	SMEMA
Conveyor belts	ESD flat belt
PCB edge support	3mm
Magazine change over time	30s (optional: 15s)
Allowable components clearance	Top 80mm, down 40mm
Magazine capacity	Top 1+down 1+ middle 1
Safety	CE certificates
Control	PLC
Voltage	220V/ 110V , single phase, 50-60Hz
Air supply	4-6 bar

GLOBAL NETWORK

FACTORYCENTER
SEOUL - BARCELONA

BUSINESSCENTER
KOREA - MEXICO - GERMANY
FRANCE - SPAIN - PORTUGAL - TUNISIA

TESTCENTER
KOREA - SPAIN - FRANCE

FACTORYCENTER
BARCELONA

Ctra. C-31, 148,4. Masia Les Planes, 20.
Camí de Les Planes. 08880 Cubelles,
Barcelona. Spain
administrative@mstechcorp.eu

BUSINESSCENTER

sales@mstechcorp.eu
services@mstechcorp.eu

