



Compatible
[SMARTBOX]
<PROCESS TRACKER>



Classic-IC-460 -UV

FEATURES

- PCB Max : 500x460
- Panasonic PLC program control
- By-pass mode, inspection mode selectable
- Conveyor width adjustment by using hand crank.(Standard).
- Center PCB stop position
- Heavy bottom design to prevent shifting
- Conveyor motor is using with stepper motor
- PCB flow direction flows can be customized
- LED light overhead frame (inspection conveyor)
- SMEMA compatible

Using SMEMA interface, this unit successfully links any SMT machine, this system can work on inspection & linking mode.

Transfer heights	900mm+/-50mm
Transfer direction	Left to right
Operation side	Front of machine
Fixed rail	Front of machine
Interface	SMEMA
Conveyor belts	ESD flat belt
PCB edge support	3mm
PCB thickness	0.5mm-2.5mm
PCB weights per boards	Max. 3kg
Allowable components clearance	top 80mm and below 25mm
Conveyor rail width	Min. 50mm to max.460mm
Inspection interval	Setting by software (optional)
Safety	CE certificates
Control	PLC
Voltage	220V/ 110V , single phase, 50-60Hz

GLOBAL NETWORK

FACTORYCENTER
SEOUL - BARCELONA

BUSINESSCENTER
KOREA - MEXICO - GERMANY
FRANCE - SPAIN - PORTUGAL - TUNISIA

TESTCENTER
KOREA - SPAIN - FRANCE

FACTORYCENTER
BARCELONA

Ctra. C-31, 148,4. Masia Les Planes, 20.
Camí de Les Planes. 08880 Cubelles,
Barcelona. Spain
administrative@mstechcorp.eu

BUSINESSCENTER

sales@mstechcorp.eu
services@mstechcorp.eu

