



Compatible
 [SMARTBOX]
 <PROCESS TRACKER>



Classic-ICW-460

FEATURES

Using SMEMA interface, this unit successfully links any machine, this system is special for connection with the wave soldering machine as the infeed conveyor, the conveyor transfer angle is available to adjusted from 4° to 7° by the hand crank wheel.

- Panasonic PLC program control
- Continuous queue feeding PCBs into the wave soldering machine.
- Conveyor width adjustment by using hand crank.
- PCB transfer angle is adjustable
- Heavy bottom design to prevent shifting
- Conveyor motor is using with stepper motor
- Conveyor transfer by chain
- PCB flow direction flows can be customized
- SMEMA compatible

Transfer heights	900mm+/-50mm
Transfer direction	Left to right
Operation side	Front of machine
Fixed rail	Front of machine
Interface	SMEMA
Conveyor belts	Chain belt
PCB edge support	5mm
Allowable components clearance	30mm below and above
Safety	CE certificates
Control	PLC
Voltage	220V/ 110V , single phase, 50-60Hz

GLOBAL NETWORK

FACTORYCENTER
 SEOUL - BARCELONA

BUSINESSCENTER
 KOREA - MEXICO - GERMANY
 FRANCE - SPAIN - PORTUGAL - TUNISIA

TESTCENTER
 KOREA - SPAIN - FRANCE

FACTORYCENTER
BARCELONA

Ctra. C-31, 148,4. Masia Les Planes, 20.
 Camí de Les Planes. 08880 Cubelles,
 Barcelona. Spain
administrative@mstechcorp.eu

BUSINESSCENTER

sales@mstechcorp.eu
services@mstechcorp.eu

