



Compatible  
**[SMARTBOX]**  
**<PROCESS TRACKER>**



## Classic-TC-460

### FEATURES

This unit is used to transfer PCBs around corners for continued process flow. Available in clock wise or counter clock wise rotation, and by-pass mode.

- PCB Max : 500x460
- Panasonic PLC program control
- By-Pass mode + 90 degree turning conveyor (Available in clock wise or counter clock wise rotation, and by-pass mode.)
- Motorized conveyor width adjustment
- LED signal tower & Buzzer
- Suitable for boards with many components on the bottom side
- Closed -loop stepper motor providing the rotating driving power
- SMEMA compatible

Transfer heights	900mm+/-50mm
Transfer direction	Left to right
Operation side	Front of machine
Fixed rail	Front of machine
Interface	SMEMA
Conveyor belts	ESD flat belt
PCB edge support	4mm
Allowable components clearance	Top 50 mm+ below 30mm
PCB inverter cycle time	Around 5s – 8s
Air supply	4-6 bar
Safety	CE certificates
Control	PLC
Voltage	220V/ 110V , single phase, 50-60Hz

## GLOBAL NETWORK

**FACTORYCENTER**  
 SEOUL - BARCELONA

**BUSINESSCENTER**  
 KOREA - MEXICO - GERMANY  
 FRANCE - SPAIN - PORTUGAL - TUNISIA

**TESTCENTER**  
 KOREA - SPAIN - FRANCE

**FACTORYCENTER**  
**BARCELONA**

Ctra. C-31, 148,4. Masia Les Planes, 20.  
 Camí de Les Planes. 08880 Cubelles,  
 Barcelona. Spain  
[administrative@mstechcorp.eu](mailto:administrative@mstechcorp.eu)

**BUSINESSCENTER**

[sales@mstechcorp.eu](mailto:sales@mstechcorp.eu)  
[services@mstechcorp.eu](mailto:services@mstechcorp.eu)

