



Compatible
[SMARTBOX]
<PROCESS TRACKER>



Classic-VL-460

FEATURES

The vacuum loader is used to load bare boards for SMT production lines. The top PCB is lifted from stack and lowered onto belt segment. The PCB stack is manually loaded into the machine and the individual PCBs are handed over to the downstream system on a transfer conveyor.

- PCB Max : 500x460
- Panasonic PLC program control
- Loader & destacker working mode can be switched exchange.
- Selectable pitch settings
- Tower-light display for machines working status.
- Flexible platform to suit standard magazines
- Exchangeable magazine from the front of machine
- Stepper motorized type pusher to enhance working stability
- Pusher position adjustable to Centre for the boards
- Use the friendly touch screen panel
- Magazine infeed and outfeed are automatically driving by motor on the platform.
- Ability to handle the bare boards by destacker.

SMEMA compatible

<PROCESS TRACKER>

Transfer heights	900mm+/-50mm
Transfer direction	Left to right
Operation side	Front of machine
Lifting platform Max. weight loading	Above 100kg
Magazine change over time	30s (optional: 15s)
Fixed rail	Front of machine
Interface	SMEMA
Conveyor belts	ESD flat belt
PCB edge support	3.8mm
Allowable components clearance	Top 50 mm+ Down 30mm
Magazine capacity	Single magazine
Safety	CE certificates
Control	PLC
Voltage	220V/ 110V , single phase, 50-60Hz
Air supply	4-6 bar

GLOBAL NETWORK

FACTORYCENTER
 SEOUL - BARCELONA

BUSINESSCENTER
 KOREA - MEXICO - GERMANY
 FRANCE - SPAIN - PORTUGAL - TUNISIA

TESTCENTER
 KOREA - SPAIN - FRANCE

FACTORYCENTER
BARCELONA
 Ctra. C-31, 148,4. Masia Les Planes, 20.
 Camí de Les Planes. 08880 Cubelles,
 Barcelona. Spain
administrative@mstechcorp.eu

BUSINESSCENTER
sales@mstechcorp.eu
services@mstechcorp.eu

