



Compatible
[SMARTBOX]
 <PROCESS TRACKER>



Classic-NGC-460 - 5P

FEATURES

This unit is used to automatically separate good boards and NG boards while allowing visual inspection for NG PCBs without any interruption on Good Board flow. It can work with any tester like AOI, SPI.

- PCB Max : 500x460
- Panasonic PLC program control
- Touch screen operation panel
- By-pass mode, inspection, NG reject mode selectable
- Conveyor width adjustment by using hand crank.
- Center PCB stop position
- Heavy bottom design to prevent shifting
- Conveyor motor is using with stepper motor
- Total 5 NG PCBs stock capability
- SMEMA compatible

Transfer heights	900mm+/-50mm
Transfer direction	Left to right
Operation side	Front of machine
Fixed rail	Front of machine
Interface	SMEMA
Conveyor belts	ESD flat belt
PCB edge support	4mm
Allowable components clearance	Top 50 mm+ below 30mm
NG PCB position length	300mm
NG PCB stock capacity	5 PCS
Max. PCB weights available	3KG
Safety	CE certificates
Control	PLC
Voltage	220V/ 110V , single phase, 50-60Hz

GLOBAL NETWORK

FACTORYCENTER
 SEOUL - BARCELONA

BUSINESSCENTER
 KOREA - MEXICO - GERMANY
 FRANCE - SPAIN - PORTUGAL - TUNISIA

TESTCENTER
 KOREA - SPAIN - FRANCE

FACTORYCENTER
BARCELONA

Ctra. C-31, 148,4. Masia Les Planes, 20.
 Camí de Les Planes. 08880 Cubelles,
 Barcelona. Spain
administrative@mstechcorp.eu

BUSINESSCENTER

sales@mstechcorp.eu
services@mstechcorp.eu

